




































Профиль	Тип	Pmax (bar)	Скорость <= (m/s)	Материал	Температура (°C)	Описание
	R	0,5	12	NBR	- 40 ... + 100°	-
	GR	1,0	15	FPM	- 20 ... + 200°	-
	L2M	0,5	30	FPM	- 20 ... + 220°	-
	SSS			AISI302		
	RB		12	NBR	- 40 ... + 100°	
	VK			NBR	- 40 ... + 100°	
	SPEEDI-SLEEVE					
	DIN 471/472					
	VA		10	NBR AF-	- 40 ... + 100°	
	VS		10	NBR AF-	- 40 ... + 100°	
	VL			NBR AF-	- 40 ... + 100°	
	VE		8	NBR AF-	- 40 ... + 100°	
	OR			NBR 70 NBR 90 FPM EPDM PTFE	- 40 ... + 110° - 40 ... + 110° - 20 ... + 200° - 55 ... + 150° - 40 ... + 200°	-
	FEP			FPM SILICON	- 20 ... + 204° - 60 ... + 204°	-
	ORN			NBR FPM SILICON EPDM	- 40 ... + 110° - 20 ... + 200° - 55 ... + 230° - 55 ... + 150°	-
	XR			NBR	- 35 ... + 110°	X-
	TR			PTFE PU NBR 90	- 100 ... + 200° - 35 ... + 110° - 40 ... + 110°	

Профиль	Тип	Pmax (bar)	Скорость <= (m/s)	Материал	Температура (°C)	Описание
	B/MD-WRR	500	0,5	NBR + POM	- 30 ... + 100°	
	TDE	500	0,5	NBR + PEE POM	- 40 ... + 110°	
	TPM	300	0,5	NBR + POM	- 40 ... + 110°	
	TPS	350	0,5	NBR + POM	- 40 ... + 110°	
	PDO	400	0,5	PU NBR POM	- 40 ... + 110°	
	PDE	700	0,5	NBR + POM	- 40 ... + 110°	
	ZX	315	0,5	PFF NBR PA	- 35 ... + 110°	
	NO	500	1,0	NBR + PA	- 40 ... + 100°	
	ZW	400	1,0	PEE NBR POM	- 35 ... + 100°	
	2	H:160 P:16	0,5 0,5	NBR	- 25 ... + 100°	
	B7	400	0,5	AU	- 35 ... + 110°	
	UNA	400	0,5	PU	- 30 ... + 100°	
	PDH	500	1,5	NBR PTFE PUN	- 30 ... + 120°	
	OK	500	1,0	PU	- 30 ... + 100°	
	KR	250	0,5	AU NBR	- 35 ... + 100°	
	OE (210)	400	4,0	PTFE (NBR)	- 40 ... + 200°	
	OG (270)	400	4,0	PTFE (NBR)	- 40 ... + 200°	
	MET	350	10,0	NBR	- 30 ... + 110°	

Профиль	Тип	Pmax (bar)	Скорость <= (m/s)	Материал	Температура (°C)	Описание
	B3	400	0,5	AU	- 35 ...+ 110°	
	BS	400	0,5	AU	- 35 ...+ 110°	
	GC	400	0,5	AU	- 35 ...+ 110°	
	BD	500	0,5	AU NBR	- 35 ...+ 110°	
	UNI	400	0,5	PU	- 35 ...+ 110°	
	C1	H:160 P:16	0,5	NBR	- 40 ...+ 100°	
	OD (170)	400	4	PTFE (NBR)	- 40 ...+ 200°	
	B/MD-E	400	0,5	NBR + POM	- 30 ...+ 100°	
	PSE	700	0,5	NBR + POM	- 35 ...+ 110°	
	R3	315	0,5	PTFE/NBR	- 30 ...+ 100°	
	ZJ	500	0,5	NBR + POM	- 40 ...+ 100°	
	M2 M3	300 500	0,5	NBR + POM	- 40 ...+ 100°	
	Q3	250	0,5	NBR + POM	- 40 ...+ 100°	

Профиль	Тип	Pmax (bar)	Скорость <= (m/s)	Материал	Температура (°C)	Описание
	UN	400	0,5	PU	- 30 ...+ 100°	
	N	H:110 P:16	0,5	NBR	- 30 ...+ 100°	
	MO CH	350	0,5	NBR + POM	- 40 ...+ 100°	
	FLEXI- SEALS					

Профиль	Тип	Pmax (bar)	Скорость <= (m/s)	Материал	Температура (°C)	Описание
	E8	16	1,0	NBR	- 20 ...+ 80°	/
	EU	16	1,0	AU	- 35 ...+ 80°	/
	EL	10	1,0	NBR	- 20 ...+ 80°	/
	E5	16	1,0	NBR	- 20 ...+ 80°	
	PP	16	1,0	NBR	- 20 ...+ 80°	( )
	E4	16	1,0	NBR	- 30 ...+ 35°	
	Z8	16	1,0	NBR	- 20 ...+ 80°	
	Z5	16	1,0	NBR	- 30 ...+ 80°	
	DK	16	1,0	NBR	- 30 ...+ 80°	

Профиль	Тип	Pmax (bar)	Скорость <= (m/s)	Материал	Температура (°C)	Описание
	GA		4	NBR	H:- 40 ...+ 100° P:-40 ...+80°C	
	AM		4	PU	H:- 40 ...+ 100° P:-40 ...+80°C	
	A5		4	NBR	H:- 40 ...+ 100° P:-40 ...+80°C	
	A1		4	NBR	H:- 40 ...+ 100° P:-40 ...+80°C	
	AY		1,0	AU	H:- 35 ...+ 100° P:-35 ...+80°C	
	AT (580)		15	PTFE (NBR)	- 40 ...+ 200°	
	AD (590)		15	PTFE (NBR)	- 40 ...+ 200°C	
	PPW		0,5	PU	- 30 ...+ 110°	